



# Lyden Oil Company

## ProGuard

### Product Information

#### **ProGuard ProCut 169P**

**ProGuard ProCut 169P** is a dark colored, non-staining, specially fortified cutting fluid that can be used in a wide range of severe-duty applications on non-ferrous and some ferrous metals.

**ProGuard ProCut 169P** is chlorine-free, and contains an effective non-staining EP agent, allowing versatility in materials machined and machining requirements.

#### **Applications:**

- Broaching
- Gear Cutting
- Gun Drilling
- Tapping
- Threading
- Hobbing
- Shaping
- Milling

#### **Typical Physical Characteristics:**

##### **ProGuard ProCut 169P**

Product Code Number	17847
Viscosity, ASTM D-88 SUS at 100° F	160
Flash Point, ASTM D-92, °F (°C)	350 (176)
Density, lbs/gal	7.63
Lubricity, %	8.9
EP Additive, %	1.1
Sulfur, %	1.2
Active Sulfur, %	0.0
Chlorine, %	0.0

#### **Lyden Oil Company**

30692 Tracy Road  
Walbridge, OH 43465

1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarps Drive  
Youngstown, OH 44515

1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906

1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317

local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646

local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com