



Lyden Oil Company

ProGuard Product Data

ProGuard Spargrind EP Honing Oil Machine Cutting Oil Product Data Sheet

ProGuard Spargrind EP Honing Oil is a light colored, low viscosity, straight oil designed for commercial honing applications. The extreme pressure additive package provides outstanding lubricity between tool and work piece resulting in excellent surface finish. **ProGuard Spargrind EP Honing Oil** is transparent so good visibility of the work is possible during machining. The product is low in odor and provides rapid settling of swarf material during honing operations.

Outstanding Features

- Light Colored, Good Visibility
- Low Odor
- Extends Tool/Stone Life

Typical Applications Include

- Honing
- Sawing
- Grinding

Physical Specifications

Color	Gold
Odor	Characteristic
Appearance	Clear
Viscosity @ 40°C Cst	3.5-4.5
Viscosity @ 100°F Sus	37.5-40.8
Specific Gravity @ 60°F	0.835
A.P.I. Gravity @ 60°F	25.0-28.0
Density (lbs/gal)	6.95
Flash Point	275°F

071116

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarps Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342