



Lyden Oil Company

ProGuard Product Data

ProGuard Sparkleen Sump Cleaner Machine Cleaning Agent Product Data Sheet

ProGuard Sparkleen Sump Cleaner will effectively clean a surface of oil, grease, hard water salts and contaminants. This product should be used before introducing new coolants and may be used prior or after discharging a sump of contaminated lubricant. **ProGuard Sparkleen Sump Cleaner** is most effective if the spent coolant is drained and a 2 to 4% solution of **ProGuard Sparkleen Sump Cleaner** in water is allowed to circulate through the machine for a minimum of 15 minutes. An alternate method is to add **ProGuard Sparkleen Sump Cleaner** to the spent coolant prior to draining. A treatment level of 3 to 5% of the total coolant volume is recommended. Recirculate this mixture for a minimum of 2 to 3 hours. After circulating, remove, and flush machine with water for 5 minutes. Immediately charge the machine with new coolant and circulate to avoid corrosion and resume normal operation.

Outstanding Features

- Good Corrosion Protection
- Bacterial Grown Inhibitors

Physical Specifications

Color	Yellow
Odor	Characteristic
Appearance	Clear, Liquid
Specific Gravity @ 60°F	1.070
Density (lbs/gal)	8.938
pH Neat Solution	11.0-13.0
Pour Point	32°F

071116

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarps Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342