



Safety Data Sheet

Lyden Oil Company

Page 1 of 8

PROGUARD Rock Drill Oil 100

SDS Number: 17913

1	PRODUCT AND COMPANY INFORMATION
----------	--

Product Name: PROGUARD Rock Drill Oil 100
Revision Date: 08/19/2015
SDS Number: 17913
Common Name: Residual petroleum oils, Heavy paraffinic oil
CAS Number: Blend
Product Code: 17913
Synonyms: Petroleum based lubricant, Rock drill oil

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515

For Product Information: 1-330-792-1100
For Emergencies: 1-800-424-9300
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Signal Word: **None**

Hazard Classes/Categories: None

Hazard Statement(s): None

Precaution Statement(s):
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.

PROGUARD Rock Drill Oil 100

SDS Number: 17913

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3 COMPOSITION / INFORMATION ON INGREDIENTSIngredients:*Mixture of the substances listed below with nonhazardous additions.*

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	70-80
Residual oils, petroleum, solvent dewaxed	64742-62-7	20-30
Olefin Sulfide	N/A	<2
Alkenyl Amine	N/A	<0.1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.*4** FIRST AID MEASURESDescription of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

Eye Contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical attention.

PROGUARD Rock Drill Oil 100

SDS Number: 17913

Symptoms and Effects, both acute and delayed:

No further relevant data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

PROGUARD Rock Drill Oil 100

SDS Number: 17913

Environmental Precautions:

Do not allow to reach sewage system or any water course.
Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material.

7 **HANDLING AND STORAGE**

Handling Precautions:

Handle with care and avoid spillage on the floor.
Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements:

Keep container tightly sealed.
Keep away from sources of ignition.

8 **EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (70-80%):

ACGIH TLV – Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.
Use safety glasses and gloves.

PROGUARD Rock Drill Oil 100

SDS Number: 17913

9 PHYSICAL AND CHEMICAL PROPERTIES

Color:	Amber
Physical State:	Liquid
Odor:	Sulfur
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>425° F
Boiling Range:	Data not available
Flash Point:	176.7° C / 350.1° F (PMCC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	100 mm ² /sec (kinematic at 40° C)

10 STABILITY AND REACTIVITYStability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and direct sunlight.

Hazardous Reactions:

No known hazardous reactions.

PROGUARD Rock Drill Oil 100

SDS Number: 17913

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not expected to form.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis or an oil acne.

Measures of Toxicity:

Component Acute Toxicity Estimates:

Residual oils, petroleum, solvent dewaxed:

Oral LD50: >5000 mg/kg (rat)

Dermal LD50: >2000 mg/kg (rabbit)

Inhalative LC50: 2.18 mg/l (4 hours) (rat)

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagenic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

PROGUARD Rock Drill Oil 100

SDS Number: 17913

13 DISPOSAL CONSIDERATIONSDisposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATIONUN Number: Data not availableUN Shipping Name: Data not availableTransport Hazard Class: Data not availablePacking Group: Data not availableEnvironmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



Safety Data Sheet

Lyden Oil Company

Page 8 of 8

PROGUARD Rock Drill Oil 100

SDS Number: 17913

16	OTHER INFORMATION
----	-------------------

Last Revision Date: 08/19/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.