

Lyden Oil Company

Page 1 of 8 -

PROGUARD Add-Tap

SDS Number: 804011

PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Add-Tap

Revision Date: 04/01/2016 SDS Number: 804011

<u>Common Name:</u> Semi-Synthetic Coolant Additive

<u>CAS Number:</u> Blend <u>Product Code:</u> 804011

Synonyms: EP / Lubricity additive

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word: WARNING

Hazard Classes/Categories:

Serious eye irritation, Category 2A. Skin irritant, Category 2.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Add-Tap

SDS Number: 804011

Hazard Statement(s):

H319: Causes serious eye irritation.

H315: Causes skin irritation.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P280: Wear protective gloves and eye protection.

P302+352: IF ON SKIN: Wash with plenty of soap and water. P332+313: If skin irritation occurs: Get medical advice/attention. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue

insing.

P337+313: If eye irritation persists get medical advice/attention. P362+364: Take off contaminated clothing and wash it before reuse.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 1 Fire = 0

Reactivity = 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Methyl Esters	67762-38-3	>50

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Lyden Oil Company

Page 3 of 8 -

PROGUARD Add-Tap

SDS Number: 804011

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical

facility.

Skin Contact:

Flush skin with water, wash with soap and water. If irritation occurs, get medical attention. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

facility for additional treatment.

Eye Contact:

Flush eyes with running water for at least 15 minutes. If redness, burning, blurred vision or irritation persists, transport to nearest

medical facility for additional treatment.

Ingestion:

Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If vomiting occurs spontaneously, keep

head below hips to prevent aspiration.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.



Lyden Oil Company

Page 4 of 8 -

PROGUARD Add-Tap

SDS Number: 804011

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Possible Hazards During a Fire:

The material as received will not support combustion, however its residues may; therefore, procedures for an oil fire should be followed.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material.



Lyden Oil Company

Page **5** of **8** -

PROGUARD Add-Tap

SDS Number: 804011

7 HANDLING AND STORAGE

Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder

container.

Storage Requirements:

Keep container tightly sealed.
Keep away from sources of ignition.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-67762-38-3 Methyl Esters:

OSHA TWA - 5mg/m3

Engineering Controls:

9

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Keep away from foodstuffs, beverages, and feed. Immediately remove all soiled and contaminated

clothing.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin. Use safety glasses and gloves.

PHYSICAL AND CHEMICAL PROPERTIES

Color: Yellow Physical State: Liquid

Odor: Characteristic
Odor Threshold: Data not available
pH: 6.7 (at 10%)
Melting Point: Data not available



Lyden Oil Company

Page **6** of **8** —

PROGUARD Add-Tap

SDS Number: 804011

Boiling Point: >212° F

Boiling Range: Data not available

Flash Point: >425° F Evaporation Rate: <1

Flammability: Data not available
Flammability Limits: Data not available
Vapor Pressure: Data not available
Vapor Density: Data not available

Relative Density: 0.9311

Solubilities: Soluble in water
Partition Coefficient: Data not available
Auto-Ignition Temperature: Data not available
Decomposition Temperature: Data not available
Viscosity: Data not available

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and

direct sunlight.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

Strong oxidizers and strong reducing agents.

Decomposition Products:

Oxides of carbon, nitrogen, and hydrogen.



Lyden Oil Company

Page **7** of **8** -

PROGUARD Add-Tap

SDS Number: 804011

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following

accidental ingestion.

Exposure Effects:

This mixture can cause irritation to skin and irritation, redness to the eyes. Prolonged and/or

repeated skin contact may cause

irritation/dermatitis.

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.



Lyden Oil Company

Page 8 of 8 -

PROGUARD Add-Tap

SDS Number: 804011

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 04/01/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.