

Lyden Oil Company

Page **1** of **8** —

1

PROGUARD SPARKUT TRI-PURPOSE

SDS Number: 809196

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD SPARKUT TRI-PURPOSE
Revision Date:	09/19/2015
SDS Number:	809196
Common Name:	Hydrotreated heavy naphthenic oil
CAS Number:	Blend
Product Code:	809196
<u>Synonyms:</u>	Machining, grinding, and cutting lubricant

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page **2** of **8** –

PROGUARD SPARKUT TRI-PURPOSE

SDS Number: 809196

Other Hazard Statement(s):

-NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>95

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:	
	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.
Skin Contact:	
	Flush skin with water, wash with soap and water. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment.
Eye Contact:	
	Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult medical attention.



Lyden Oil Company

Page 3 of 8	Lyach on compa
	PROGUARD SPARKUT TRI-PURPO
SDS Number: 809196	
	ith water. If symptoms develop, obtain medical
attention.	
Symptoms and Effects, both acute and delayed:	No further relevent data available.
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	
	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting
	an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	
	Hazardous combustion products may include: A
	complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide.
	Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	
	Proper protective equipment including breathing apparatus.
6 ACCIDENTAL RELEASE MEASU	IKES

Personal Precautions:

Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.



Lyden Oil Company

Page 4 of 8	
	PROGUARD SPARKUT TRI-PURPOSE
SDS Number: 809196	
Emergency Procedures:	Contain spilled material, collect in suitable and
	properly labled containers.
Environmental Precautions:	
	Do not allow to reach sewage system or any water
	course.
	Do not allow to enter ground waters.
Cleanup Procedures:	
	Pick up excess with inert absorbant material. Treat
	contaminated absorbent same as spilled product.
7 HANDLING AND STOR	ACE
TIANDEING AND STOR	
Handling Precautions:	
	Handle with care and avoid spillage on the floor.
	Do not cut, weld, drill, grind, braze, or solder
	container.
Storage Requirements:	
	Keep container tightly sealed.
	Keep away from sources of ignition.
8 EXPOSURE CONTROLS	S / PERSONAL PROTECTION
Exposure Limits:	
	llates (petroleum), hydrotreated heavy naphthenic (>95%):
ACGIH TLV – Shor	t-term value: 10mg/m ³
Long-term value:	
OSHA PEL – Long-	term value: 5mg/m ³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).



Lyden Oil Company

Page 5 of 8 -

9

PROGUARD SPARKUT TRI-PURPOSE

SDS Number: 809196

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

PHYSICAL AND CHEMICAL PROPERTIES

Color: Physical State:	Amber Liquid
Odor:	Characteristic
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>500° F
Boiling Range:	Data not available
Flash Point:	385° F
Evaporation Rate:	<1 (where Butyl Acetate - 1)
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.8803 (where water = 1)
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	36 mm ² /sec (kinematic at 40° C)

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		Stable under normal conditions.
<u>Reactivity:</u>		Not reactive under normal conditions.
Conditions to Av	void:	
		Extreme temperature, sparks, open flame, and direct sunlight.



Lyden Oil Company

Page 6 of 8	
	PROGUARD SPARKUT TRI-PURPOSE
SDS Number: 809196	
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	Strong oxidizers and strong reducing agents.
Decomposition Products:	Oxides of carbon, and hydrogen.
11 TOXICOLOGICAL INFORMATIC	DN
Routes of Exposure:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
<u>Exposure Effects:</u>	Repeated skin contact may cause dermatitis or an oil acne. Exposure to eyes may cause redness. Harmful if swallowed, may cause burns to mouth and esophagus.
Measures of Toxicity:	No test data available.
Carcinogenic/Mutagenic Precautions:	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMATION	
Ecological Precautions:	Avoid exposing to the environment.

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.



PROGUARD SPARKUT TRI-PURPOSE

Lyden Oil Company

SDS Number: 809196

13 DISPOSAL C	ONSIDERATIONS	
Disposal Methods:		Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containers:		Use properly approved container for disposal.
Special Precautions:		Do not flush to surface waters or drains.
14 TRANSPORT	INFORMATION	
<u>UN Number:</u> <u>UN Shipping Name:</u> <u>Transport Hazard Class:</u> Packing Group:	Data not available Lubricating Oil, N.O Data not available Data not available).S.
Environmental Hazards:		Data not available
Bulk Transport Guidance:		Data not available
Special Precautions:		Not regulated by DOT.
15 REGULATOR	RY INFORMATION	

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

Page **7** of **8** –



Lyden Oil Company

Page 8 of 8 -

PROGUARD SPARKUT TRI-PURPOSE

SDS Number: 809196

16 OTHER INFORMATION

Last Revision Date: 09/19/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.